B100SLF Panel Mount Status Beacon [Filament Lamp]



The B100 series is comprised of a Xenon strobe beacon, permanent filament bulb, blinking filament bulb and a permanent LED array beacon version.

The panel mount base incorporates a pluggable terminal block ensuring rapid installation and maintenance.

Features


- Bayonet fixing lens.
- Anti-tamper locking screw.
- Stainless steel fixings.

Approvals

• GOST-R certificate: POCC GB.JB05.H00144.







Specification

Light source:	Filament lamp BA9s
Light output:	5W
Function:	Permanent
Lens colours:	Amber, Blue, Clear, Green, Red & Yellow
Lens type:	Prismatic (standard) or plain
Candela:	5 cd* (peak/effective intensity)
Mounting:	Panel mount PG29
Ingress protection:	IP65
Housing material:	High impact UL94 V0 (f1) PC
Terminals:	0.5 to 1.5mm² pluggable
Operating temp:	-25 to +50°C [-13° to +122°F]
Storage temp:	-40 to +70°C [-40° to +158°F]
Relative humidity:	90% at 20°C [68°F]
Weight:	93g/2.04lbs

*Candela measurements representative of performance with clear lens at optimum voltage.

Part Codes

Version: 12-250V	W attage: 5W	Part code: B100SLF250B/[x]	
[x] = Lens colo	ur:	A: Amber B: Blue C: Clear G: Green R: Red Y: Yellow	
NOTE: Filamer	nt lamps not included.		

AUTHORIZED DISTRIBUTOR: GasDetectorsUSA.com Houston, Texas USA sales@GasDetectorsUSA.com 832-615-3588

E2S Warning Signals 15 Dec 2014