

# BExCP3A-PT/BExCP3B-PT Tool Reset Call Point

The SIL 2 compliant BExCP3A-PT and BExCP3B-PT push button, tool resettable manual call points are approved for Zone 1, 2, 21 and 22 hazardous areas for the control of fire and gas alarm systems.

Available with and without monitoring resistors all versions are certified to ATEX and IECEx standards. The push button mechanism is protected by a spring loaded cover therefore the switch requires a two-action activation. The push button is user resettable via the use of the special key supplied with the unit. The BEx range features enclosures manufactured from corrosion proof, marine grade, copper free LM6 (A413) aluminium with a chromate and powder coat finish.

## Options

- Alternative housing colours are available to meet specific requirements.
- DIN rail mounted terminal blocks: 8 × 2.5mm<sup>2</sup>
- Metalised Polyester "Duty" label.
- Series and/or End of Line resistors.

## Approvals

- ATEX certificate: Sira 09ATEX3286X, IEC 60079-0:2007 Ed 5, EN 60079-1:2004, EN 60079-7:2007, IEC 60079-18:2009 Ed 3, EN 61241-1:2004
- IECEx certificate: IECEx SIR 09.0121X, IEC 60079-0:2007-10 Edition: 5, IEC 60079-1:2003 Edition: 5, IEC 60079-18:2009 Edition: 3, IEC 60079-7:2006-07 Edition: 4, IEC 61241-1:2004 Edition: 1
- INMETRO certificate: 10HEx-0011X
- GOST-R certificate: POCC GB.JB05.B03365
- SIL 2 certified to IEC 61508 (2010)



## Specification

BExCP3A-PT:	II 2G Ex d e IIC T6 Gb II 2D Ex t IIIC T60°C Db IP66
BExCP3B-PT:	II 2G Ex d e mb IIC T4 Gb II 2D Ex t IIIC T70°C Db IP66
Ambient:	Ta = -40°C to +55°C [-40° to +131°F] (+50°C for BExCP3B)
Ingress protection:	IP66
Enclosure material:	Marine grade copper free LM6 Aluminium
Enclosure finish:	Chromated & powder coated finish: anti-corrosion.
Colour:	RAL3000 Red (others available on request)
Cable entries:	2 x M20 clearance top and 1 x M20 clearance side. Back box can be rotated to give 2 x bottom and 1 x side entries.
Stopping plugs:	2 x Ex e nylon plugs as standard Brass and stainless steel plugs optional
Terminals:	6 × 4.0mm <sup>2</sup> cables or or 8 × 2.5mm <sup>2</sup> DINrail

## Part Codes

Option:	Code:	Description:
Type:	BExCP3A-PT BExCP3B-PT	A type – no end of line devices B type – choice of end of line devices
Terminals:	ST DR	ST: Standard DR: DINrail (only on BExCP3B type)
Duty label:	NL DL	No duty label Duty label required – specify contents
Colour:	RD XX	Red enclosure colour Other enclosure colour – contact sales
Voltage:	48V 24V 12V 6V	System voltage (only required for BExCP3B type)
E.O.L. Resistor:	ExxxR	Resistor value in Ohms e.g. E470R = 470 Ohm (only required for BExCP3B type)
Series Resistor:	SxxxR	Resistor value in Ohms e.g. S1K5R = 1.5K Ohm (only required for BExCP3B type)
Accessories:	SP65-0001-A2 SP65-0001-A4 SP65-0002-A2 SP65-0002-A4	Pole Mount Bracket Kit 2" St/St A2 (304) Pole Mount Bracket Kit 2" St/St A4 (316) Sunshade – St/St A2 (304) Sunshade – St/St A4 (316)

## Versions

Version:	Voltage:	Switch:	Terminals:	Cable entries:	
BExCP3A-PT	250V ac Max. 50V dc Max.	5.0A Max. 1.0A Max.	6 × 4mm <sup>2</sup>	2 x M20 Top/Bottom 1 x M20 Left/Right	
<b>Coding:</b>	II 2G Ex d e IIC T6 Gb Ta = -40°C to +55°C II 2D Ex t IIIC T60°C Db IP66				
Version:	Nom./Max. Voltage:	Switch:	Terminals:	Cable entries:	Min. EOL / Series Value:[]
BExCP3B-PT	48V/56V 24V/28V 12V/15V 6V/9V	56V dc Max. Rating: <50V: 1.0A >50V: 0.75A	6 × 4mm <sup>2</sup> or 8 × 2.5mm <sup>2</sup> DINrail	2 x M20 Top/Bottom 1 x M20 Left/Right	1K8 470R 120R 47R