



### Description

- Removes contaminants as low as 1-micron
- Removes water and particles
- Does not remove or deplete additives

### Used For

- Hydraulic Oil
- Engine Oil
- Transmission Oil
- Cutting Oil
- Other low viscosity oil-based lubricants
- Diesel Fuel

### Capacity & Flow Rate

- Requires 20 Qt./18.9 L. of makeup fluid (housing volume)
- \*Ideal sump range from 16-250 Gal./60.6-946.4 L.  
Lube 16-22 Gal./60.6-83.3 L.  
Hydraulic 151-250 Gal./571.6-946.4 L.
- \*\*Flow rate: See chart

### Specifications

- Beta<sub>3</sub>=250
- Max operating pressure 80 PSI
- Overall dimensions 19.75" (H), 7.5" (D)
- Fits part # 900102, 900101, 900358, 900372, 900243, 900865, 900320, 900188, 900186, 900245, 900265, 900267, 900269, 900281, 900280, 900368, 900033, 900035
- Used with petroleum or synthetic fluids & diesel fuel

### Notes

- \*\*Flow rates are established using ISO 10-32 viscosity oils at the standard 40° C/104° F and are subject to vary
- \*Viscosity, operating temperature, and generated contamination will affect sizing and flow rates of filtration equipment
- Most applications, elements need to be changed between 500-1000 hours for optimal performance, ideally change the element when the flow is half the starting flow or the PSI is double the starting PSI
- The max dirt & water capacities are determined when the flow is reduced by half the original flow (*this is the optimal operating condition*)

30PSI	70°F/21.1°C	104°F/40°C	150°F/65.6°C
10	2.75G/10.41L	4G/15.14L	4.25G/16.09L
15	1.83G/6.91L	3.5G/13.25L	4.75G/17.98L
22	1G/3.79L	2G/7.57L	3.60G/13.63L
32	.88G/3.31L	1.38G/5.2L	3.25G/12.30L

\*\*Chart data **G—Gallons Per Minute, L—Liters Per Minute**

\*\*Flow chart (at high temperatures, ISO 10-22 oils max out at lower than 30 PSI)

### Recommended Viscosities

- Diesel
- ISO: 10, 15, 22, 32
- SAE: 5W, 10W

**Harvard Corporation is able to meet many custom requirements, please contact us with you specific custom needs**