



HA72 SPECIFICATIONS

Gas Detection Controller

General Specifications	
Use	Wall or rack/panel mountable digital gas controller for industrial or commercial use
Display	QVGA 320 x 240 pixel graphic LCD with backlight; displays bar graphs, trends and engineering units in color Five discrete LEDs indicate alarm status for five standard alarm relays
Ethernet Port	Modbus TCP Master/Slave port
Alarm Relays	5 amp 30VDC or 250VAC resistive Form C
Analog Inputs (OPTIONAL)	12 bit 4-20mA into 150 ohms input impedance; includes +power supply terminal for each channel for routing power to two or three wire transmitters
Analog Output (OPTIONAL)	10 bit 4-20mA output; max load 800 ohms with nominal 24VDC power supply
Serial Port (OPTIONAL)	Master and Slave RS-485 half or full duplex ports equipped with Tx / Rx LEDs Protocol = Modbus RTU
Power Requirement	10 – 30VDC (24VDC nominal) 12 Watts max
Operating Temperature Range	-13°F to +140°F (-25°C to +60°C)
Housing Options	NEMA 4X fiberglass wall mount ½ length 19" rack / panel mount Full length 19" rack mount
Weight	Panel mount ½ 19" rack: 8 lbs. Full 19" rack: 12 lbs Compact Fiberglass: 26 lbs Large Fiberglass: 75 lbs Large 316 Stainless Steel: 88 lbs
Warranty	12 months from date of commissioning or 18 months from date of delivery, whichever is less
Ratings and Certifications	
	Class I, Div. 2, Groups A, B, C and D CAN/CSA-C22.2 No.152-M1984 ANSI/ISA-12.13.01-2000 CSA-C22.2 No. 213-M1987 UL Std No. 1604, Third Ed. – 1994 ANSI/ISA-12.12.01-2010

Find out more

www.honeywellanalytics.com

Toll-free: 800.538.0363

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

SS01155_V1 12/12

© 2012 Honeywell Analytics